

# 601.220 Intermediate Programming

Writing functions, command-line arguments

# Outline

- Functions we write ourselves
- Exercise 6

# Functions

Same idea as Java methods, Python functions

We've called functions (`printf`, `scanf`, `isalpha`, ...), but haven't defined any of our own

# Functions

```
int foo(char c, int i) {  
    return i;  
}
```

int foo

- foo is the *name*
- int is the *return type*

(char c, int i)

- This is the *parameter list*
- char c and int i are *parameters*.

Everything inside { curly braces } is the body

# Communication between functions

- For functions to communicate, we use function parameters and/or function return values
  - External (global) variables are another option; though use of these is discouraged except in specific circumstances

# Function definitions and function calls

```
float func1 (int x, float y) {  
    return x+y;  
}
```

Calls to above function definition:

```
int a = 7;  
float b = 2.5;  
  
float c = func1(a,b);  
  
float d = func1(a,c);  
  
float e = func1(a+2,3.5);
```

- Different calls to function match different arguments with the formal parameters x and y

# Functions

A function returning nothing has return type `void`, and does not need a `return` statement

```
void say_hello() {  
    printf("Hello, World!\n");  
}
```

If there are no parameters, parameter list written as `()` or `(void)`

## Function examples

```
int add(int lhs, int rhs) {  
    int sum = lhs + rhs;  
    return sum;  
}  
  
double convert(double fahrenheit) {  
    return 5.0 / 9.0 * (fahrenheit - 32.0);  
}
```

# Checkpoint Question!

Given the function definition, which function call is invalid in C?

```
int abs(int a) {  
    if (a < 0)  
        return -a;  
    return a;  
}
```

- A. `abs(2 / 5);`
- B. `int c = 0; abs (c);`
- C. `abs('%');`
- D. `abs (-2.2);`
- E. None of the above

# Checkpoint Question!

Which function name(s) below is/are guaranteed to be valid in C?

- A. `function_092`
- B. `fun$12`
- C. `5fun2`
- D. `func68`
- E. A and D

# Functions

"Experience has shown that the best way to develop and maintain a large program is to construct it from smaller pieces or modules, each of which is more manageable than the original program."

- Deitel & Deitel Chapter 5 intro
- Rule of 30: <https://dzone.com/articles/rule-30-%E2%80%93-when-method-class-or>

# Functions

Factoring your code into functions – instead of putting everything in `main` – has major advantages:

- Keeps you concentrating on smaller problems, one at a time
- Makes code more readable
- Helps with testing
  - Can test *functions* one by one
  - Tests are easy to write; call function with certain inputs, assert something about return value
- Easier to collaborate
  - “I’ll write function X, she writes function Y, you write everything else assuming you have X and Y.”

# Functions

Putting a chunk of code in a new function is appropriate when:

- The code has a clear, distinct goal
- The number of variables used in the snippet is not large
- The code has a single result (or not very many)

# Parameter passing

- Argument values in C are passed by value
  - function is given argument values in temporary variables (not originals)
  - therefore, function can not directly modify an argument variable back in the calling function
  - [... MORE ON THIS NEXT CLASS...]

## Command-line arguments

When you type `mkdir cs220`, you're running a program called `mkdir` and passing it a single *command-line argument*, `cs220`

C programs can take arguments similarly, but you have to declare your `main` function in a special way...

# Command-line arguments

```
// args_eg_1.c:  
#include <stdio.h>  
  
int main(int argc, char* argv[]) {  
    printf("argc = # arguments + 1: %d\n", argc);  
    for(int i = 0; i < argc; i++) {  
        printf("argv[%d] = %s\n", i, argv[i]);  
    }  
    return 0;  
}  
  
$ gcc args_eg_1.c -std=c99 -pedantic -Wall -Wextra  
$ ./a.out rosebud  
argc = # arguments + 1: 2  
argv[0] = ./a.out  
argv[1] = rosebud
```

# Command-line arguments

```
int main(int argc, char* argv[])
```

- `int argc` is a parameter that equals the number of command-line arguments. The program name (e.g. `./a.out`) counts as the first.
- `char* argv[]` is an array of strings. The strings are the command-line arguments.
  - Might also see `char argv[][]` or `char **argv`; these all mean the same thing

# In-Class Exercise

- Work on Exercise 6
  - Complete it before next meeting